



FERRO-BET WIRE-GREASE

Wire grease deeply penetrates the wire with no need to heat. It creates a surface film with significant staple capacity and prevents water and dirt from penetrating. A dry wire needs a second application as the first application penetrates to the core.

If you are using Masto lubricator you do not need lubrication twice. Masto press the grease deep into the core of Wiers the first application. Masto lubricator provides interior cleaning and lubrication by use of pressure. This can prolong the life of the wire by as much as 100-200%.

The wire grease will not turn to liquid at any temperature below 90 degree Celsius and will not turn brittle until it reaches negative 40 degree celsius. The product color is light and will not color off on other surfaces. Wire Grease is perfect for all working wires like life boat wire, screws, bolts, tie-up wire, closing screws, the drive wheels in the anchor game and everywhere else requiring an effective rust preventive grease. It comes ready to use It can be thinned with White Spirit or a similar product. Apply with Masto lubricator, or the old style, with a glove or by submersion.





FERRO-BET WIRE-GREASE

Product information

Produkt : Ferro-Bet Wire Grease

Property	Method	Typical
NLGI Grade	ISO 2137	0
Density 20 °C	IPPM-CS/03	0,91
Colour	Visual	Light yellow
Appearance	Visual	smooth
Base oil kinematic viscosity at 40°C, mm ² /s	ISO 12058/	
DIN 53015	60	
Base oil kinematic viscosity at 100°C, mm ² /s	ISO 12058/	
DIN 53015	6	
Dropping point, °C	IP 396	min140
Worked penetration at 25°C after 60 strokes, dmm	ISO 2137	355-385
Change in worked penetration at 25°C after 100000 strokes, dmm	ISO 2137	35
Copper corrosion	24 h at 100°C	ASTM D4048
1b		
SKF Emcor corrosion test	dist water	ISO 11007
0-0		
SKF Emcor corrosion test salt water	ISO 11007	2-2

Ferro-Bet Wire Grease is an anhydrous calcium thickened lubricating grease based on mineral oil. The grease contains antioxidants and corrosion inhibitors.

The low viscous base oil makes the product suitable for low temperature applications. The grease is also suitable for roller bearings operating at high speed.

Ferro-Bet Wire Grease is a high quality grease that can be used in both industrial and automotive applications. The grease is suitable for a wide range of plain and rolling bearings.

Good corrosion protection

Good low temperature performance

Suitable for high speed applications

Corrosion protection

SKF Emcor distilled water ISO 11007 0-0

SKF Emcor salt water ISO 11007 2-2

Copper corrosion 24h/100°C ASTM D4048 1b



SPECIAL APPLICATION



CORROSION PROTECTION



LOW TEMPERATURE